

Insulating rope tool offering excellent dielectric properties and designed for performing live work on AC or DC energized apparatus.

Meets or exceeds the dry or wet electrical requirements of :

- IEC 62192:2009
- ASTM F1701-12

Arc-Flash rated

- Resistant to 40 cal/cm² (category 4)

Features

- Unique insulating properties
- Cleanable and easy to maintain and test
- Exceptionally low leakage current, whether dry or wet
- Protection from high fault current
- High strength
- Low elongation
- Lightweight and low volume
- Fully sealed and hydrophobic
- Smooth surface
- High abrasion resistance
- Easy to deploy
- Excellent resistance to UV
- High visibility sealed termination at each end
- Comes with transport bag



Transport bag included

Barry Cordage Ltd.

6110 boul. des Grandes Prairies
Montreal QC H1P 1A2 Canada
☎ 514.328.3888 📠 514.328.1963
1.800.305.2673 (Canada / USA)

www.barry.ca

Copyright © 2022 Barry Cordage Ltd.
Barry has a policy of continuous improvement and reserves the right to update product or components without prior notice.
UNCONTROLLED IF PRINTED



SPECIFICATIONS

- **Working Load Limit:** 200 lb (90 kg)
- **Diameter:** 1/4" (6 mm)
- **Terminations:** Stainless steel thimble at each end
- **Colour:** Black with bright orange terminations
- **Weight:** 0.78 lb (0.35 kg) for 20' length
- **Standard Lengths:** 20' (6.1 m), 30' (9.1 m), 40' (12.2 m)

Note: Available in other lengths. Contact Barry for more information.

Barry D.E.W. Line® and all Barry D.E.W Line® products are trademarks of Barry Cordage Ltd. Use of these trademarks is strictly prohibited unless authorized by Barry.