

Insulating rope tool which may serve as a replacement for FRP strain link sticks during temporary installations in energized fields and high voltage systems (AC or DC).

Meets or exceeds the dry or wet electrical requirements of:

- IEC 62192:2009
- ASTM F1701-12

Arc-Flash rated

- Resistant to 40 cal/cm² (category 4)

Features

- Unique insulating properties
- Cleanable and easy to maintain and test
- Exceptionally low leakage current, whether dry or wet
- Protection from high fault current
- High strength
- Low elongation
- Lightweight and low volume
- Fully sealed and hydrophobic
- Smooth surface
- High abrasion resistance
- Easy to deploy
- Excellent resistance to UV
- Sealed termination at each end, with choice of closed or open spelter sockets
- Comes with transport bag



Transport bag included

Barry Cordage Ltd.

6110 boul. des Grandes Prairies
Montreal QC H1P 1A2 Canada
☎ 514.328.3888 📠 514.328.1963
1.800.305.2673 (Canada / USA)

www.barry.ca

SPECIFICATIONS

- **Working Load Limit:** 15 000 lb (6 804 kg)
- **Diameter:** 1-1/4" (32 mm)
- **Terminations:** Closed or open spelter sockets
- **Colour:** Black
- **Weight:** 35 lb (15.9 kg) for 15' length w/ closed spelters
50 lb (22.7 kg) for 15' length w/ open spelters
- **Standard Lengths:** 10' (3.0 m), 15' (4.6 m), 20' (6.1 m)
(Other lengths available upon request)

HL-NK38000C: Closed spelter socket both ends

HL-NK38000O: Open spelter socket both ends

HL-NK38000X: Closed spelter socket/open spelter socket